

What is claimed is:

- Svbat
- 666240-T40000
1. Method for operating a chemical and/or physical process in a vessel containing a liquid, a gas and/or solid particles, in which vessel a fluid is introduced through a hierarchical network of channels comprising parent and child generations of channel formations, wherein substantially each channel in a parent generation is divided into N channels of the child generation, whereby each of said child generations may in turn be a parent generation for a successive child generation, which network terminates in channel exits, such that said fluid is discharged from the channel exits substantially uniformly throughout the vessel volume.
2. Method according to claim 1 in which said network is a self-affine network of channels, wherein each of the channels in the parent generation have a diameter d_j and length l_j , and each of the channels in the child generation have a diameter d_{j+1} and length l_{j+1} , wherein the ratios d_j/d_{j+1} and/or the ratios l_j/l_{j+1} , are substantially constant for channels of successive generations running in parallel direction or in which method said network is a self-similar network which is a type of said self-affine network wherein the ratios d_j/d_{j+1} and l_j/l_{j+1} are substantially constant for channels of successive generations independent of their direction.
3. Method according to claim 2 wherein the ratios of diameters and/or lengths of channels in successive generations of said network are related to N by

$$N = (d_j/d_{j+1})^\Delta, \text{ and/or}$$

$$N = (l_j/l_{j+1})^D,$$

wherein Δ and D represent an integer or a real positive number.

- SUSP
4. Method according to claim 3 wherein D is between
2 and 3.
5. Method according to claim 1, in which said chemical
and/or physical process is selected from a group consisting
of a fluidized bed process, a slurry process, an absorption
process, a gas/liquid bubble column process and an aeration
process.
6. Method for scaling up chemical and/or physical
processes which processes are carried out in a vessel
10 comprising the steps of building a small scale vessel in
which vessel a fluid is introduced through a hierarchical
network of channels comprising parent and child generations
15 of channel formations, wherein substantially each channel in
a parent generation is divided into about N channels of the
child generation, which network terminates in channel exits,
such that said fluid is discharged from the channel exits
substantially uniformly throughout the vessel volume and
determining optimal geometry and optimal values for the
parameters N, Δ and D, and subsequently building a large
20 scale vessel in which said geometry and parameters are
substantially the same as in the small scale vessel.
7. Vessel containing a hierarchical network of channels,
said network comprising parent and child generations of
channel formations, wherein substantially each channel in a
25 parent generation is divided into N channels of the child
generation, whereby each of said child generations may in
turn be a parent generation for a successive child
generation, which network terminates in channel exits,
wherein said network is a self-affine network of channels,
30 wherein each of the channels in the parent generation have a
diameter d_j , and length l_j , and each of the channels in the
child generation have a diameter d_{j+1} and length l_{j+1} , wherein
the ratios d_j/d_{j+1} and/or the ratios l_j/l_{j+1} are substantially
constant for channels of successive generations running in

SEARCHED INDEXED
SERIALIZED FILED

Sub A1

parallel direction or in which vessel said network is a self-similar network which is a type of said self-affine network wherein the ratios d_j/d_{j+1} and l_j/l_{j+1} are substantially constant for channels of successive generations independent of their direction.

8. Vessel according to claim 7 wherein the ratios of diameters and/or lengths of channels in successive generations of said network are related to N by

$$N = (d_j/d_{j+1})^\Delta, \text{ and/or}$$

10 $N = (l_j/l_{j+1})^D,$

wherein Δ and D represent an integer or a real positive number.

9. Vessel according to claim 8 wherein D is between 2 and 3.

15 10. Hierarchical network of channels comprising parent and child generations of channel formations, wherein substantially each channel in a parent generation is divided into N channels of the child generation, whereby each of said child generations may in turn be a parent generation for a successive child generation, which network terminates in channel exits, which said network is a self-affine network of channels, wherein each of the channels in the parent generation have a diameter d_j and length l_j , and each of the channels in the child generation have a diameter d_{j+1} and length l_{j+1} , wherein the ratios d_j/d_{j+1} and/or the ratios l_j/l_{j+1} are substantially constant for channels of successive generations running in parallel direction or which network is a self-similar network which is a type of said self-affine network wherein the ratios d_j/d_{j+1} and l_j/l_{j+1} are substantially constant for channels of successive generations independent of their direction and wherein the ratios of diameters and/or

SEARCHED INDEXED
SERIALIZED FILED

Sub A2

Subas

lengths of channels in successive generations of said network are related to N by

$$N = (d_j/d_{j+1})^A, \text{ and/or}$$

$$N = (l_j/l_{j+1})^D,$$

5 wherein A and D represent an integer or a real positive number.

11. Network according to claim 10 wherein D is between 2 and 3.

12. Network according to claim 10 wherein at least one material is present near the exits of said network and/or said material is present as a coating on at least part of the inner surface of said network, which material is capable of chemical and/or physical interactions with fluids.

13. Network according to claim 10 which is provided with 15 means for obtaining a gradient in the dimensions of the respective exits.

Add a 4

SEARCHED INDEXED
SERIALIZED FILED
APR 16 1990